

AXIS 295 Video Surveillance Joystick

Easy joystick control of Axis PTZ and PTZ dome network cameras.



- > Cost-efficient solution
- > Durable high quality USB-joystick
- > Easy to install and configure
- > Three-axis joystick
- > Twelve programmable push-buttons

AXIS 295 Video Surveillance Joystick is a cost-efficient USB device, specifically designed for responsive and accurate control of all Axis PTZ and PTZ dome network cameras.

The AXIS 295 Video Surveillance Joystick is equipped with an USB cable and thus very easy to install. Just connect the joystick to the USB port and it is up and running, controlling all the Axis PTZ and PTZ dome cameras. No proprietary protocols or protocol converters needed.

It features a three-axis, durable (Hall-effect) joystick with X/Y-axis for positioning and turning knob for zoom.

The joystick comes with twelve programmable push-buttons: two on top of the handle and ten on the base.

The AXIS 295 integrates seamlessly with any video surveillance software platform that supports Axis cameras and joystick inputs via Microsoft's DirectX.



Technical specifications – AXIS 295 Video Surveillance Joystick

General	
Performance	Hall-effect joystick with three axes X/Y: for camera view positioning Z: for zoom in and out Push-buttons: two on top of the handle and ten on the base Joystick travel: X/Y-axis $\pm 18^\circ$, Z-axis $\pm 40^\circ$ Centering: single spring, omni directional
Housing	High impact ABS Handle: high impact glass reinforced nylon Boot: thermoplastic rubber Shaft: stainless steel Suitable for right- and left-handed use
Power	Via USB interface (5V DC) Supply current: 32 mA
Operating conditions	-25 to 85 °C (-13 to 185 °F)
Approvals	EN 55024:1998, EN 55022, FCC Part 15 Subpart B Class B
Dimensions H x W x L	127 x 157 x 168 mm (5.0" x 6.2" x 6.7")
Weight	440 g (1.0 lb.)
Connection	USB port, connected directly to the workstation/PC Uses the standard DirectX drivers
Connectors	USB A
System integration Support	Windows XP, 2003 and 2000
Application support	AXIS Camera Station 2.10 and above Selected AXIS Partner software applications* AXIS Media Control when controlling PTZ cameras via Internet Explorer *See www.axis.com/partner/adp_program for more software applications via partner
Supported protocols	USB 2.0**, DirectX (Gaming control) **Backwards compatible with USB 1.x
Accessories (included)	Blank text sheets for push-buttons, plastic covers for text sheet
Applications (not included)	Supported by AXIS PTZ video products with firmware version 4.40 or later

More information is available at www.axis.com/accessories

Dimensions

