


TRANSFORMER TX/30D 230V / 12-24VAC 30VA

Transformer with 230V primary winding, 0-12-24V / 30 VA secondary winding for intermittent use on 24 V output. Dimensions: 87,5x100x65 mm (5 DIN modules).



Compatibility

Simplebus Color system:	Yes
Simplebus 2 system:	Yes
Traditional system:	Yes
Simplified system:	Yes
Comelbus system:	Yes
Comtel system:	Yes

Mounting/Installation

Wall-mounted:	Yes
Surface-mounted:	Yes
DIN rail mounted:	Yes
DIN modules (no.):	4

Audio/video specifications

Audio system:	Yes
Audio/video system:	Yes

Connectivity

Stabilised output:	No
--------------------	----

Technical properties

Temperature range:	0 / 40 C
--------------------	----------

Electrical specifications

AC supply voltage:	230 V
Switching power supply:	No
Alternating voltage output A (V):	12

DATA SHEET

Alternating voltage output B (V):	24
Maximum current absorption (mA):	180
Maximum power delivered:	30 VA

General info

EAN product code:	8023903000184
Product height (mm):	90
Product width (mm):	71,7
Product depth (mm):	62

Packaging

Single pack height (mm):	76
Single pack width (mm):	86
Single pack weight (g):	772
Single pack depth (mm):	96