

Description: 22 AWG 4/C STR OAS CM-CL2
Specifications: UL Standards 13 & 444; NEC Article 725 & 800

Construction:

Conductor 22 AWG 7/0.0096 Stranded Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk,Red,Wht,Grn
Insulation Diameter 0.042 nom.
Lay Length 1.5" nom.
Drain Wire 24 AWG 7/32 Tinned Copper
Shield 0.001" Thick Aluminum/Mylar

Jacket PVC
Jacket Thickness 0.015" nom.
Outside Diameter 0.139" nom.
Legend (Ink Print) **HONEYWELL P/N 1204 4C22 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US
SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E
F 1 2 3 4 5 6 7 8 9**

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 28 pf/ft nom.
Impedance 53 Ohms nom.
DC Resistance 16.5 Ohms/M' at 20°C
Flame Rating UL 1685 Vertical Tray